



# Saturn 1000KC

Castles Technology's newly designed SATURN1000KC next generation 4G desktop device offers multifunctional capabilities and optimizes the checkout process for your business. It comes with several optional features including 4G LTE/3G, Wi-Fi, Bluetooth, microphone, and front camera.

The SATURN1000KC is based on a secure Android platform and has integrated contactless reader function with a 4" full touchscreen. The SATURN1000KC is an extremely easy, safe and secure for merchants looking for a next generation payment device.

4" Color Touch Screen

Secure Android Platform

Front Camera

# FEATURES & BENEFITS

## Unprecedented Security and Certifications

- PCI PTS 5.x
- EMV Contact/ Contactless Lv1
- EMV Contact Lv2
- Contactless Scheme Certifications (PayPass, payWave, Expresspay, D-PAS, J-Speedy, QuickPass...)

## Incredibly Adaptable

- Optional dial-up modem function
- Accepts all payment types
- Flexible to integrate business applications

## Exceptional Performance

- High Security Processor
- Operable under extreme conditions
- Android open architecture OS

# SATURN 1000KC



## SPECIFICATIONS

		SATURN1000KC	
<b>Processor</b>		High Speed Quad-Core Processor plus Secure MCU	
<b>Operating System</b>		Android 7.0	
<b>Memory</b>	Flash/RAM	8GB/1GB (Up to 16GB/2GB)	
<b>Display</b>		4" 480 x 800 Color TFT LCD with Capacitive Touch Display	
<b>Card Reader</b>	Magnetic Stripe	ISO 7810, 7811, 7813 Triple Track, Bi-Directional	
	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
		SAM Card	1 (up to 2)
		SIM Card	2
	Contactless	ISO 14443 Type A, B   ISO 18092 NFC   Mifare and Sony FeliCa Working Frequency 13.56MHz	
<b>Communications Interface Options</b>	Wire	RS232   USB   LAN	
	Wireless	4G LTE/3G/GPRS   Wi-Fi   Bluetooth	
	GPS	Yes	
<b>Indicators</b>	Audio	Speaker and 4 Pole Audio Jack + Microphone	
<b>PIN Pad</b>		Build-in PIN Pad	
<b>Thermal Printer</b>		57mm x 50mm	
<b>Camera</b>		2M Fixed Front Camera	
<b>Software</b>		SDK   KMS   TMS   CTOS library ISO 8583 library   Crypto library	
<b>Crypto</b>		TRNG   DES   TDES   AES   RSA   MK/SK   DUKPT	
<b>Power Supply</b>	DC	9V/3.3A	
<b>Environment</b>	Operating Temperature	0°C to 50°C	
	Storage Temperature	-20°C to 70°C	
	Operating Humidity	5% to 90% non-condensing	
	Storage Humidity	5% to 90% non-condensing	
<b>Certification</b>		PCI PTS 5.X   EMV L1/L2   payWave   PayPass   Expresspay   D-PAS Interac Flash   J-Speedy   FeliCa   UnionPay UICS   TQM	
<b>Optional Features</b>		Dial-up modem	